

# LAYLINES

Modular Tile

## Construction

Tufted, Textured Loop

## Tile Size

50 cm x 50 cm (19.7" x 19.7")

## Yarn Type

Milliken-Certified WearOn® Nylon  
Type 6,6

## Stain Resist / Soil Release

StainSmart®

## Dye Method

PrintWorks™ Precision Dyeing

## Gauge

1/10

## Stitches Per Inch

14.4

## Tufts

144/in<sup>2</sup> (2,230/100 cm<sup>2</sup>)

## Standard Backing

PVC-Free WellBAC® Comfort Cushion  
Available with TractionBack®

## Recycled Content by Total Weight

Standard Backing: 40.9% Pre-Consumer, 0.0% Post-Consumer  
NSF 140 Platinum Backing Option: 30.0% Pre-Consumer, 11.0% Post-Consumer

## Embodied Carbon

13.39 (kg CO<sub>2</sub>e)/m<sup>2</sup>

## Nominal Total Thickness

0.31" (7.9 mm)

## Nominal Total Weight

86.7 oz/yd<sup>2</sup> (2,940 g/m<sup>2</sup>)

## Flammability (Radiant Panel

**ASTM-E-648)**

≥ 0.45 (Class I)

## Smoke Density (NFPA-258-T or

**ASTM-E-662)**

≤ 450

## Methenamine Pill Test (CPSC FF-1-70

**or ASTM D 2859**

Self-Extinguishing

## Lightfastness (AATCC 16E)

≥ 4.0 at 80 Hours

## Crocking (AATCC 165)

≥ 4.0 Wet or Dry

## Static Electricity (AATCC-134) 20% R.H., 70° F.

≤ 3.5 KV, Permanent Conductive Fiber

## Texture Appearance Retention Rating (TARR)

Severe Traffic End-Use Applications

## Recommended Maintenance

MilliCare® Textile and Carpet Care Service Network

## Indoor Air Quality—CRI Green Label Plus™

GLP0793, Carpet Category 5Y

## Recommended Installation Method(s)

Vertical Ashlar; Modular Zoning Components: Monolithic

## WARRANTIES

Lifetime Face Fiber Wear

Lifetime Antistatic

Lifetime Floor Compatibility

Lifetime Color Pattern Permanency

Lifetime Floor Release

Lifetime Cushion Resiliency

Lifetime Moisture Resistance

Lifetime Delamination of Backing

Lifetime Staining/Soiling (StainSmart®)

Lifetime Dimensional Stability

Lifetime Tuft Bind

Lifetime Edge Ravel

Flammability



**Declare.**



This cushion-back carpet tile product is covered by one or more patents, published applications and/or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.